



The **RWE** wall canopy



Ultra-slim timeless design

Robinhood RWE 600/900 Wall Canopy

At home in any kitchen

Simple yet elegant, the straight lines and right angles of this slender design will complement your kitchen décor for years to come.

Sophisticated lighting

Twin 'fish eye' frosted halogen lights provide a modern look and let you see your way to cooking success.

Three-speed extraction

Powerful centrifugal fan can be set to low, medium or high to match your cooking styles. Steam vegetables, stir-fry spices and sear steaks without thinking twice.

Fingertip control

Push buttons make lighting and fan speed selection a breeze, so you can focus on your cooking.

Efficient easy-clean filters

Four-layer micromesh filters trap grease effectively. They're simple to remove and are easily maintained with a regular clean in the dishwasher.

Recirculation if you can't duct

In situations where ducting isn't possible, this rangehood can be fitted with charcoal filters that cleanse the air effectively before returning it to the kitchen.

Turns off if the worst happens

If you have a cooking disaster, and something catches fire, the rangehood automatically switches off to prevent flames and sparks being sucked into the ducting or ceiling.

Product incorporates a thermal overload function that senses extreme heat and disconnects power to the motor temporarily.



Extraction	Gross Airflow: Up to 736m ³ per hour extraction power.* Net Airflow: Up to 650m ³ per hour extraction power. <small>*The airflow figures are calculated to the IEC61591 standard and includes a 10% tolerance due to motor performance variations.</small>
Finish	Stainless steel.
Lighting	Halogen lighting.
Filter	Multi-layered micromesh. Dishwasher safe.
Decibel rating	Speed 1: 58.5 dB. Speed 2: 63.3 dB. Speed 3: 67.7 dB.
Ducting	Round 150mm ducting outlet. Recirculation option available.
Charcoal Filter Code	2536: 2 pack (600 model) 2537: 3 pack (900 model)
Chimney Extensions (fits both models)	2611: 3048mm/10ft 2612: 3658mm/12ft
Safety	Automatic shut off if flames are detected. Fire retardant plastic parts.
Models	RWE3CH6SS: 600 model RWE3CH9SS: 900 model
Dimensions	



See Wall Canopy Operation and Installation instructions on our website for further information on ducting and recirculation.



Due to ongoing research and development, the manufacturer reserves the right to change specifications without notice. If specifications are important to end use, please ask your merchant. Terms and conditions are subject to change without notice. Brochure issued January 2010.

New Zealand 0800 760 667 www.robinhood.co.nz
Parbury Building Products (NZ) Limited

Australia 1800 648 556 www.robinhood.com.au
Parbury Pty Limited ABN 63104298062

